





OPTIMA Series



Plugs and sockets for industrial applications

PLUGS

	Current rating	No of poles	Hr position	Voltage AC	☐	Cat. No.	
						IP44	IP66/IP67
	20A	2P+E	6	200-250	50	213.2033-SF	-
		2P+E		200-250	10/50	213.2033	-
		3P+E		380-415	10/50	213.2036	-
		3P+N+E		346-415	10/50	213.2037	-
	32A	2P+E	6	200-250	10/40	213.3233	-
		3P+E		380-415	10/40	213.3236	-
		3P+N+E		346-415	10/40	213.3237	-
	63A	2P+E	6	200-250	6/24	213.6333	-
		3P+E		380-415	6/24	213.6336	-
		3P+N+E		346-415	6/24	213.6337	-
	20A	2P+E	6	200-250	10/40	-	218.2033
		3P+E		380-415	10/40	-	218.2036
		3P+N+E		346-415	10/40	-	218.2037
	32A	2P+E	6	200-250	10/40	-	218.3233
		3P+E		380-415	10/40	-	218.3236
		3P+N+E		346-415	10/40	-	218.3237
	63A	2P+E	6	200-250	6/24	-	218.6333
		3P+E		380-415	6/24	-	218.6336
		3P+N+E		346-415	6/24	-	218.6337
125A	3P+N+E	6	346-415	1/8	-	218.12537	

☐ Pack/Quantity

CONNECTORS

	Current rating	No of poles	Hr position	Voltage AC	☐	Cat. No.	
						IP44	IP66/IP67
	20A	2P+E	6	200-250	50	313.2043-SF	-
		2P+E		200-250	10/50	313.2043	-
		3P+E		380-415	10/50	313.2046	-
		3P+N+E		346-415	10/50	313.2047	-
	32A	2P+E	6	200-250	10/40	313.3243	-
		3P+E		380-415	10/40	313.3246	-
		3P+N+E		346-415	10/40	313.3247	-

☐ Pack/Quantity

CONNECTORS



Current rating	No of poles	Hr position	Voltage AC	⌀	Cat. No.	
					IP44	IP66/IP67
20A	2P+E	6	200-250	10/40	-	318.2043
	3P+E		380-415	10/40	-	318.2046
	3P+N+E		346-415	10/40	-	318.2047
32A	2P+E	6	200-250	10/40	-	318.3243
	3P+E		380-415	10/40	-	318.3246
	3P+N+E		346-415	10/40	-	318.3247
63A	2P+E	6	200-250	6/24	-	318.6343
	3P+E		380-415	6/24	-	318.6346
	3P+N+E		346-415	6/24	-	318.6347
125A	2P+E	6	346-415	1/8	-	318.12547

⊠ Pack/Quantity

FLUSH MOUNTING SOCKET OUTLETS






Current rating	No of poles	Hr position	Voltage AC	⌀	Cat. No.	
					IP44	IP66/IP67
20A	2P+E	6	200-250	10/100	413.2063	-
	3P+E		380-415	10/100	413.2066	-
	3P+N+E		346-415	10/100	413.2067	-
32A	2P+E	6	200-250	10/50	413.3263	-
	3P+E		380-415	10/50	413.3266	-
	3P+N+E		346-415	10/50	413.3267	-
63A	2P+E	6	200-250	6/30	413.6363	-
	3P+E		380-415	6/30	413.6366	-
	3P+N+E		346-415	6/30	413.6367	-
20A	2P+E	6	200-250	10/100	-	418.2063
	3P+E		380-415	10/100	-	418.2066
	3P+N+E		346-415	10/100	-	418.2067
32A	2P+E	6	200-250	10/50	-	418.3263
	3P+E		380-415	10/50	-	418.3266
	3P+N+E		346-415	10/50	-	418.3267
63A	2P+E	6	200-250	6/30	-	418.6363
	3P+E		380-415	6/30	-	418.6366
	3P+N+E		346-415	6/30	-	418.6367
125A	3P+N+E	6	346-415	1/10	-	418.12567

⊠ Pack/Quantity

OPTIMA Series


Plugs and sockets for industrial applications

■ SURFACE MOUNTING SOCKET OUTLETS

	Current rating	No of poles	Hr position	Voltage AC	☒	Cat. No.	
						IP44	IP66/IP67
	20A	2P+E	6	200-250	10/40	513.2053	-
		3P+E		380-415	10/40	513.2056	-
		3P+N+E		346-415	10/40	513.2057	-
	32A	2P+E	6	200-250	10	513.3253	-
		3P+E		380-415	10	513.3256	-
		3P+N+E		346-415	10	513.3257	-
	20A	2P+E	6	200-250	10/40	-	518.2053T
		3P+E		380-415	10/40	-	518.2056T
		3P+N+E		346-415	10/40	-	518.2057T
	32A	2P+E	6	200-250	10	-	518.3253T
		3P+E		380-415	10	-	518.3256T
		3P+N+E		346-415	10	-	518.3257T
	63A	2P+E	6	200-250	6/12	-	515.6353
		3P+E		380-415	6/12	-	515.6356
		3P+N+E		346-415	6/12	-	515.6357
	125A	3P+N+E	6	346-415	1/8	-	515.12557

☒ Pack/Quantity

■ ACCESSORIES

	Description		☒	Cat. No.
	Blank plate for panel cutouts	70x87 mm	25	654.0100

☒ Pack/Quantity